VERDERLUBE Media Media Viso Viso Viso Viso Viso Viso Viso Viso	VERDERLOBE Glycerine based lubricant for Verderflex <sup>1</sup> ubre peristaltic hose pumps. Mide No. Volume B 129,149 B 129,149 B 129,149 Compared to the second B 129,149 Compared to the second Compared to the second Com	VERDERLUBE® Glycerine based lubricant for Verderflex® other peristaltic hose pumps. Article No. Volume (Urres) Article No. Volume EF 129.1419 1 C EF 129.142 Sef 129.1420 5 EF 120. 10	<b>ト レ ト ト ト</b>

## VERDERLUBE

# Special lubricant for Verderflex®

ACCORDING TO DIRECTIVE 91/155/EC EDITION FEBRUARY 2011 DOCUMENT VERSION JULY 2014



Find you local supplier at **www.verderflex.com** or scan the QR code



## CONTENTS

1	<b>Identific</b> 1.1 1.2	ation of the substance/preparation and of the company/undertaking Identification of substance or preparation Company identification	3 3 3
2	Composi	tion / information on ingredients	3
3	Hazardo	us identification	3
4	First aid	measures	4
-	4.1	Ingestion	4
	4.2	Inhalation	4
	4.3	Skin contact	4
	4.4	Eye contact	4
5	Fire fight	ting measures	4
	5.1	Extinguishing media	4
	5.2	Extinguishing media to avoid	4
	5.3	Unusual fire and explosion hazards	4
	5.4	Special protective equipment for fire fighters	4
6		al release measures	5
	6.1	Personal protection	5 5
	6.2	Environmental precautions	5 5
	6.3	Methods for cleaning up	5
7	Handling 7.1	<b>y and storage</b> Handling	5 5
	7.1	Storage	5
	7.2	Storage	
8	-	e controls / personal protection	5
	8.1	Personal protection	5
	8.2	Occupational exposure limits	5
9	Physical	and chemical properties	6
10	-	and reactivity	6
		Conditions to avoid	6
		Materials to avoid	6
	10.3	Hazardous decomposition products	6
11		gical information	7
		Toxicity data	7
	11.2	Significant data with possible relevance to human health	7
12		al information	7
		Mobility	7
		Persistence and degradability Bio accumulative potential	7 7
		Aquatic toxicity	7
13	Disposal	considerations	8
15	-	Waste disposal method(s)	8
_			
14	Transpo	rt information	8
15	15 Regulatory information		8
16	Other inf	formation	8

# Verderlube is the lubricant / coolant used with the Verderflex<sup>®</sup> range of and other peristaltic or hose pumps

#### WARNING



Used lubricant may become contaminated with pumped product, also verify precautions and advice against relevant product information

Verderlube is a food grade product in accordance with FDA CFR 21 part 178 :3570 Lubricant with Incidental Food Contact and complies with EC Regulation 1935/2004

## 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY / UNDERTAKING

#### **1.1** Identification of Substance or Preparation

Product name	Verderlube
Chemical identification	Glycerine based blend
Cas number	Preparation
Use	Food Grade - Pump Lubricant / Coolant

Verder Limited

#### **1.2** Company Identification

Producer / supplier

	Unit 3 California Drive
	Castleford
	WF10 5QH
	Great Britain
Tel number	+44 (0) 1924 221 020
Fax number	+44 (0) 113 246 5649
Emergency tel number	
For advice on this product call:	+44 (0) 01924 221 020

## 2 COMPOSITION / INFORMATION ON INGREDIENTS

- This product contains no substances classified as hazardous to health in concentrations that should be taken into account according to EC directive 91/155/EC
- Main constituent may cause irritation to eyes and skin.
- Irritating to respiratory system in the form of a mist.

## **3 HAZARDOUS IDENTIFICATION**

This product is not classified as hazardous according to EC directive 91/155/EC

## WARNING

- - May cause irritation to eyes and skin.
  - Irritating to respiratory system in the form of a mist.
  - Contact with hot product may cause burns.
  - Product is a lubricant and in the event of untreated spillage, can cause external surfaces to become slippery when wet

## 4 FIRST AID MEASURES

Used lubricant may become contaminated with pumped product, also verify precautions and advice against relevant product information

## 4.1 Ingestion

- Give 500 ml of Water to drink
- DO NOT INDUCE VOMITING!
- Except as a deliberate act, the ingestion of large amounts of product is unlikely. If this should occur, do not induce vomiting, obtain medical advice.

#### 4.2 Inhalation

 If inhalation of fumes from overheated material causes irritation to the nose or throat, or coughing, remove to fresh air. Obtain medical advice if any symptoms persist.

#### 4.3 Skin Contact

- Wash thoroughly with mild soap and water as soon as reasonably practical.
- Remove heavily contaminated clothing and wash underlying skin

#### 4.4 Eye Contact

- Wash eye thoroughly with copious amounts of water, ensuring eyelids are held open.
- Obtain medical advice if any pain or redness develops or persists.

## **5 FIRE FIGHTING MEASURES**

Used lubricant may become contaminated with pumped product, also verify precautions and advice against relevant product information

#### 5.1 Extinguishing Media

Alcohol resistant foam, dry powder or water fog

## 5.2 Extinguishing Media To Avoid

Do not use water jets

#### 5.3 Unusual Fire and Explosion Hazards

Avoid spraying directly into storage containers because of danger of boil over

#### 5.4 Special Protective Equipment for Fire fighters

- Protective clothing and approved breathing apparatus when in close proximity of fire
- During burning, poisonous acrolein may be found.

## **6** ACCIDENTAL RELEASE MEASURES

Used lubricant may become contaminated with pumped product, also verify precautions and advice against relevant appropriate product information

#### 6.1 Personal Protection

 Wear goggles and gloves. If spillage has occurred in a confined space, ensure sufficient ventilation and check that a safe, breathable atmosphere is present before entry.

#### 6.2 Environmental Precautions

• Protect drains from spills and prevent entry of product. Treated effluent may be biodegradable. Recover cleaning water for later treatment..

#### 6.3 Methods for Cleaning Up

Contain and recover liquid, soak up with absorbent material (sand, peat, etc.) or contain and shovel into drums or containers. Remove residue by spraying with water.

## 7 HANDLING AND STORAGE

Used lubricant may become contaminated with pumped product, also verify precautions and advice against relevant product information

#### 7.1 Handling

- Contact with hot product causes burns.
- Avoid contact with eyes. If splashing is likely to occur wear a full visor or chemical goggles to appropriate local national standards.
- Avoid frequent or prolonged skin contact with fresh or used product.
- Wash hands thoroughly after use.

#### 7.2 Storage

Store under cover away from moisture and sources of ignition. Do not overheat in storage. The lubricant/coolant is hygroscopic; keep the container tightly closed.

## 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

#### 8.1 Personal Protection

- Contact with hot product causes burns.
- Avoid contact with eyes. If splashing is likely to occur wear a full visor or chemical goggles to appropriate local national standards.
- Avoid frequent or prolonged skin contact with fresh or used product.
- Wash hands thoroughly after use.

#### 8.2 Occupational Exposure Limits

- Ensure good ventilation.
- Threshold limit Not tested

## 9 PHYSICAL AND CHEMICAL PROPERTIES

Form	Viscous liquid
Colour	Blue. Colourless may be supplied to special order
Odour	Odourless
Solidification point	-40°C / -40°F approx.
Flash point	177°C / 350°F approx. (COC: ISO 2592)
Boiling point	290°C / 554°F
Solubility in water	Miscible (at 20°C)
Vapour pressure	(20°C / 68°F) <0.01 mBar
	(100°C / 210°F) <1 mBar
Viscosity	700 mPaS approx. @ 20°C / 68°F
рН	7 approx.
Auto ignition temperature	400°C / 750°F approx.
Explosion limits	Not established
Density (20°C/68°F)	1245 kg/m <sup>3</sup> approx.
Behaviour with water at 20°C	Hygroscopic

## **10 STABILITY AND REACTIVITY**

Used lubricant may become contaminated with pumped product, also verify precautions and advice against relevant product information

#### **10.1** Conditions to Avoid

Preparation is stable and unlikely to react in a hazardous manner under normal conditions of use.

- No special precautions other than good housekeeping of chemicals.
- Hazardous polymerisation reactions are unlikely to occur.
- This material is combustible.

## **10.2** Materials to Avoid

 Avoid contact with strong oxidizing agents, nitrogenous compounds and strong acids: risk of violent and or explosive reactions with pure compounds.

#### **10.3 Hazardous Decomposition Products**

- During burning, poisonous acrolein may be found very toxic by inhalation.
- Incomplete combustion / thermal decomposition will generate smoke, carbon dioxide and hazardous gases, including carbon monoxide.

## **11 TOXICOLOGICAL INFORMATION**

Used lubricant may become contaminated with pumped product, also verify precautions and advice against relevant product information

#### 11.1 Toxicity Data

- General purpose food grade lubricant /coolant
- LD<sub>50</sub> oral (rat) 12600 mg/kg (not harmful) \*

#### **11.2** Significant Data with Possible Relevance to Human Health

- Eyes Unlikely to cause more than transient stinging or redness if accidental eye contact occurs
- Skin Unlikely to cause harm to the skin
- Ingestion Unlikely to cause harm if accidentally swallowed in small doses, although larger quantities should be avoided
- Inhalation At ambient temperatures this product will be unlikely to present an inhalation hazard

## **12 ECOLOGICAL INFORMATION**

Used lubricant may become contaminated with pumped product, also verify precautions and advice against relevant product information

#### 12.1 Mobility

 Spillage may penetrate the soil; unused preparation is food grade and is inherently harmless.

#### 12.2 Persistence and Degradability

• This preparation is inherently biodegradable

#### 12.3 Bio Accumulative Potential

There is no evidence to suggest that bioaccumulation will occur.

#### 12.4 Aquatic Toxicity

- Verderlube is miscible in water. It is not considered harmful in low concentrations.
  Water pollution reactors gO<sub>2</sub>/g
  BOD<sup>5</sup>: 0,87 (NEN 3235-5.4)
  BOD<sup>1</sup>: 1.16 (NEN 3235-5.3)
  Fish: goldfish LC50 (24h):>5000 mg/l (modified ASTM D1345)
- The aquatic toxicity (TLm<sub>96</sub>) is >1000mg/l, which is defined by NIOSH as an insignificant hazard.

## **13 DISPOSAL CONSIDERATIONS**

Used lubricant may become contaminated with pumped product, also verify precautions and advice against relevant product information

#### 13.1 Waste Disposal Method(s)

- Where possible, arrange for unused product to be recycled.
- Disposal of preparation should be via an authorized person/licensed waste disposal contractor in accordance with local regulations.
- Incineration may be carried out under controlled conditions provided that local regulations are met.
- Dispose of preparation and container carefully and responsibly. Do not dispose of preparation near ponds, ditches, down drains onto soil.

#### **14 TRANSPORT INFORMATION**

Not classified as dangerous for transport (RID/ADR-ADNE-IATA-IMDG-MARPOL-ICAO)

## **15 REGULATORY INFORMATION**

Classification - Classification not required

#### **16 OTHER INFORMATION**

- Employees of the Verder group have not experienced any harmful effect during normal handling and production.
- Verderlube<sup>®</sup> and Verderflex<sup>®</sup> are registered trademarks.

The information contained in this sheet is based on our knowledge of the preparation at its delivery date and that the information contained herein is current as of the date of this data sheet. Since the use of this information and of these opinions and the conditions of use of this preparation is not within the control of Verder Limited, it is the user's obligation to determine the conditions of safe use of the preparation.



The information contained in this sheet is based on our knowledge of the product at its delivery date